2C

YAMAHA

2CMHS



Specifications		
Engine Type	1-Cylinder	
Displacement	50 cm3	
Bore x Stroke	42 x 36 mm	
Compression ratio	8.3:1	
Starting enrichment	Manual Choke	
Scavenging	Loop Charging	
Fuel induction system	1-Carb	
Lubrication system	Pre-mixed Fuel and Oil	
Oil-Fuel Mixing Ratio	50:1	
Engine oil capacity	-	
Ignition system	CDI	
Ignition timing	BTDC 18^0 (Fixed)	
Spark plug	B7HS	
Alternator	-	
Cooling system	Raw-water, thermostatically controlled	
Exhaust system	Under water	
Dry weight	10Kg	
Features		**MH**
Security	Start in gear protection	-
	Engine stop switch lanyard	-
	Over rev. limiter	-
	Over heat warning	-
Corrosion prevention	Stainless steel waterpump housing	●
	Chrome plated water pump housing	-
	Stainless steel water tube	-
	Single large anode	●
	Corrosion free resin propeller	●
Power unit	Carburetor	●
	Gasoline (Regular)	●
Convenience	Carrying handle	-
	Integral fuel tank	●
	2-way fuel supply system	-
	360 deg. full pivot steering	●
	Shallow water drive	-